



Autoprint Formula Solution Pvt. Ltd.

Alphaline 155 UV RC-FG

Drip-off effect texture roller coating gloss topcoat (fine grain)

March 2021

Product description

This coating is recommended to be used in combination with matt base coating offset to get texture effect. The UV matt coating 165 is used as a base coat using offset plates, to select areas to be printed.

The UV texture gloss roller coating is applied over the UV texture matt base coat as well as on the whole surface of the print.

As a result, areas covered only with the glossy area appear glossy and the area above the texture matt base coat creating texture effect. Thus, these results an interesting optical contrast effect with fine grains.

Technical specification

Application:	Roller coater (flexo printing unit)
Colour:	Pale straw clear liquid
Print substrate:	Printed paper and board/Met-Pet
Dry solid content:	Approx. 100%
Viscosity by Ford cup at 30°C:	35 -45 sec.

Note:

- Preliminary adhesion tests are recommended prior to commercial run. Always shake well before use.
- Hot foil stamping may do (Where alone AL155 UV is applied and will depend on the quality of foil).
- Avoid coating process on tonner-based oil based conventional ink printed Job.

Products safety

This product is not recommended for low migration and low odour requirement.

The Printer have the legal responsibility to ensure that the finished article is fit for the intended purpose and that ink & coating components do not migrate into the food at levels that exceed legal and industry requirements.

Shelf life

6 months from the date of manufacturing if it is stored in sealed container below 25 °C away from heat & sunlight.

Precautions

Avoid contact of UV Coating with skin and eyes. We recommend use of disposable gloves and protective goggle.

Disclaimer

This information is furnished without warranty, expressed, or implied, except that it is accurate to the best knowledge of Afosol Private Limited. The data on the sheet is related to specific product designated herein. Afosol Private Limited assumes no legal responsibility for use or reliance upon these data.

Contact details

AFOSOL	Autoprint Formula Solution Pvt. Ltd.
Office:	No 7, North Huzur Road, Coimbatore 641018
Support:	Phone +91 422 221 2416/+91 422 221 6750
E-mail:	support@afosol.com
Webpage:	www.afosol.com