

Alphaline 96 UV RC

High gloss UV curable roller coating

July 2021

Product Description

Alphaline 96 UV RC is a UV curable coating designed for roller coat application in-line over UV curable inks or off-line over dried conventional inks.

It can be applied on a wide range of papers and boards. Product has good slip and surface wetting characteristics, high gloss, and good curing speed.

Technical characteristics

Viscosity by Ford Cup B4 @ 30°C	47 ± 3 sec
Application (coater systems)	Roller coater system (anilox, chambered doctor blade systems)
Color & Appearance	Pale straw liquid
Gloss on white coated board by gloss meter @ 60°	>90 gloss points
Print tested in lab	Using bar coater No.1 (Minimum film thickness applied 4 g/m²)
Substrate	Printed board
Coating's lay	Good
Curing parameter in lab test	One medium pressure Hg vapor UV lamp of 300 watt, with conveyer speed of 70 m/min.
Odour of cured coating	Characteristic odor after immediate printing. After 24 h, odour vanishes

Note:

- 1. Preliminary adhesion tests are recommended prior to commercial run.
- 2. Always shake well before use.
- 3. Not recommended for foil stamping operation.
- 4. Avoid coating process on tonner-based oil based conventional ink printed Job.

Storage and handling

Product safety: This product is not recommended for low migration and low odour requirement. The Printer/Converter/Packer have the legal responsibility to ensure that the finished article is fit for the intended purpose and that ink & coating components do not migrate into the food at levels that exceed legal and industry requirements.

Shelf life: Shelf life of UV OPM is 6 months from the date of manufacturing if it is stored in sealed container below 25 °C away from heat & sunlight.

Precautions: Avoid contact of UV Coating with skin and eyes. We recommend use of disposable gloves and protective goggle.



Disclaimer

This information is furnished without warranty, expressed, or implied, except that it is accurate to the best knowledge of Afosol Private Limited.

The data on the sheet is related to specific product designated herein. Afosol Private Limited assumes no legal responsibility for use or reliance upon these data.

Contact details

AFOSOL	Autoprint Formula Solution Pvt. Ltd.
Office:	No 7, North Huzur Road, Coimbatore 641018
Support:	Phone +91 422 221 2416/+91 422 221 6750
E-mail:	support@afosol.com
Webpage:	www.afosol.com